

1.8 KVA PETROL GENERATOR

FEATURES & BENEFITS

- Maximum 2.0 kVA, 230V, Smart Throttled RPM
- Inverter Type (Automatic Voltage Regulator)
- Recoil Starter
- 4 Litre Fuel Tank, 4 Hours @ 75% load
- Silent "Suitcase" Type Version (± 67 dBA)
- Single Cylinder, Forced Air-Cooling, 4-stroke
- Single Phase Output
- 3-in-1 Display Meter Digital
- DC Output for battery Charging
- Colours May Vary



Colours may vary.

GENERAL DATA	
Model:	BP2000IS-II
Prime Power (P.R.P):	1.8 kVA
Stand-by Power (L.T.P):	2.0 kVA
Amps:	8.6 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	Smart Throttled RPM
Length:	464 mm
Width:	296 mm
Height:	456 mm
Weight:	20 kg's
Tank Capacity:	4 l

ADDITIONAL	
Running Time:	4 Hours @ 75% load
Structure Type:	Silent "Suitcase" Type
Noise Level (7m):	67 dBA
Auto Voltage Regulator:	Inverter Type
ISO9001 Certified:	Yes
CE Certified:	Yes
Fuel Cons. @ 100% Load:	1.4
Fuel Cons. @ 75% Load:	1.0
Fuel Cons. @ 50% Load:	0.6

ENGINE DATA	
Brand:	Genkins
Model:	LT80i
Type:	Single Cylinder, Forced Air-Cooling, 4-stroke
Starting System:	Recoil Starter
Auto-Decompression:	Yes
Cubic Capacity (l):	0.079
Compression Ratio:	8.8:1
Rated Power (kW/RPM):	2kW
Fuel Type:	Petrol
Lube Oil:	10W-30 / SAE30
Low Pressure Alert:	N/A
Low Fuel Cut Out:	N/A

CONTROL PANEL	
Model:	3-in-1 Display Meter
Type:	Digital
Analogue Inputs:	N/A
Mains Phase Voltage:	No
Mains Line Voltage:	No

ALTERNATOR	
Model:	
Pole Number:	N/A
Excitation Mode:	

Contact: Mike de Castro
Cell No: 078 095 4453

* Specs subject to change without prior notice.
 * Measurements based on ISO8528-1 Standards
 * All rating at Sea Level, 25°C Ambient Temp.