

7.5 KVA PETROL GENERATOR

FEATURES & BENEFITS

- Maximum 8.0 kVA, 230V, 3000 RPM
- Yes (Automatic Voltage Regulator)
- Electric & Recoil
- 28 Litre Fuel Tank, 6 Hours @ 75% load
- Open Version (± 74 dBA)
- Single cylinder, air-cooled, 4-stroke, OHV
- Single Phase Output
- 3-in-1 Display Meter Digital
- Robust wheels, handle and frame
- Electric or Pull Start



GENERAL DATA

Model:	BP8000-OP
Prime Power (P.R.P):	7.5 kVA
Stand-by Power (L.T.P):	8.0 kVA
Amps:	34.7 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	3000 RPM
Length:	720 mm
Width:	530 mm
Height:	610 mm
Weight:	87 kg's
Tank Capacity:	28 l

ADDITIONAL

Running Time:	6 Hours @ 75% load
Structure Type:	Open
Noise Level (7m):	74+ dBA
Auto Voltage Regulator:	Yes
ISO9001 Certified:	Yes
CE Certified:	Yes
Fuel Cons. @ 100% Load:	5.9
Fuel Cons. @ 75% Load:	4.2
Fuel Cons. @ 50% Load:	2.9

ENGINE DATA

Brand:	Genkins
Model:	GK460 - Air Cooled
Type:	Single cylinder, air-cooled, 4-stroke, OHV
Starting System:	Electric & Recoil
Auto-Decompression:	Yes
Cubic Capacity (l):	0.458
Compression Ratio:	
Rated Power (kW/RPM):	8.2 kW
Fuel Type:	Petrol
Lube Oil:	10W-30
Low Pressure Alert:	Yes
Low Fuel Cut Out:	Yes

CONTROL PANEL

Model:	3-in-1 Display Meter
Type:	Digital
Analogue Inputs:	N/A
Mains Phase Voltage:	No
Mains Line Voltage:	No

ALTERNATOR

Model:	
Pole Number:	2
Excitation Mode:	

Contact: Mike de Castro
Cell No: 078 095 4453

* Specs subject to change without prior notice.
 * Measurements based on ISO8528-1 Standards
 * All rating at Sea Level, 25°C Ambient Temp.